## CLAIM AMENDMENTS:

- (Currently Amended) A method of construction for concrete beams or walls comprising the steps of:
- (a) setting rows of a plurality of boxing modules in an end to end relationship to create a formwork,
  - (b) fastening abutting ends of the modules, and
- (c) spacing the formwork by a plurality of spacers which span between the module panels and are fixed by bolts, or push-in ties,
- (d) bracing and straightening the formwork as required,
- (e) setting reinforcing between the formwork as required, and
  - (f) pouring concrete into the formwork.
- 2. (Original) A method as claimed in claim 1 wherein the spacers may be hollow tubular members or push-in ties.
- 3. (Original) A method as claimed in claim 1 wherein the boxing modules are joined utilising slots in side and end walls of the modules.
- 4. (Original) A method as claimed in claim 1 wherein the quick release clamping devices are used to join the side and end walls of the modules.
- 5. (Original) A method as claimed in claim 1 wherein the quick release clamping device is a wedge.
- 6. (Original) A method as claimed in claim 1 wherein the quick release clamping device is a strap which joins respective ends of the modules and sets the spacings between the modules.
- 7. (Original) A method as claimed in claim 1 wherein the individual modules comprise a rectilinear front face, a

peripheral border wall extending from the front face, two spaced pairs of bolt sockets in major surfaces of the modules and a plurality of opposed slots in the peripheral border walls of the modules.

7.

- 8. (Original) A method as claimed in claim 1 wherein some of the panels of the formwork are joined and others are not.
- 9. (Original) A method as claimed in claim 1 wherein the inner walls of the modules or panels are used to create designs or patterns in a formed wall.
- 10. (Original) A method as claimed in claim 1 wherein the formwork is reinforced by elongate straps or beams.
- 11. (Original) A method as claimed in claim 10 wherein elements of the straps or beams are adjustable to increase the strength of same.
- 12. (Original) A method as claimed in claim 1 wherein the modules are joined together in a staggered formation.
- 13. (Original) A method of creating a formwork for a horizontal column from a plurality of modules, supporting the formwork from a surface below and integrating the columns with a floor slab.
- 14. (Original) A formwork comprising a plurality of joined boxing modules in an end to end relationship wherein each boxing modules has front and rear faces and a continuous peripheral flange about the rear face said flanges having openings therein so that the boxing modules can be united via the flanges using quick release clamping devices.
- 15. (Original) A formwork as claimed in claim 14 wherein the joined boxing modules are made parallel by a plurality of spacers spanning between the modules.

- 16. (Original) A formwork as claimed in claim 14 wherein the quick release clamping devices are wedges.
- 17. (Original) A formwork as claimed in claim 14 wherein the quick release clamping devices are straps.
- 18. (Original) A formwork as claimed in claim 14 wherein the formwork is braced and stiffened by elongate braces.
- 19. (Original) A formwork as claimed in claim 18 wherein the braces are vertical, horizontal or angular.
- 20. (Original) A formwork as claimed in claim 14 wherein the boxing modules are rota-moulded.
- 21. (Original) A formwork as claimed in claim 20 wherein two modules are formed together with rota-moulding and then separated on removal from a mould.
- 22. (Original) A formwork as claimed in claim 20 wherein the modules are provided with integral or external stiffening members.
- 23. (Original) A formwork as claimed in claim 14 including vertical and horizontal reinforcing bars which extend from the ends and top and bottom surfaces of the formwork.

## 24 - 25. (Cancelled)